

## User guide Industrial display



<b>1</b>	Power button	Press the power button to turn the device on or off. Press and hold the power button to enter the power-off menu.
<b>2</b>	Home button	Press the home button to return to the home screen.
<b>3</b>	Back button	Press the back button to return to the previous screen.
<b>4</b>	Volume up/down buttons	Press the volume up/down buttons to adjust the volume.
<b>5</b>	Micro-USB port	Connect the Micro-USB cable to the Micro-USB port to charge the device or transfer data.
<b>6</b>	Headset jack	Connect a headset to the headset jack.
<b>7</b>	Power button	Press the power button to turn the device on or off. Press and hold the power button to enter the power-off menu.
<b>8</b>	Volume up/down buttons	Press the volume up/down buttons to adjust the volume.
<b>9</b>	Micro-USB port	Connect the Micro-USB cable to the Micro-USB port to charge the device or transfer data.
<b>10</b>	Headset jack	Connect a headset to the headset jack.

Pin	Signal	Function
1	VCC	Power supply
2	GND	Ground
3	TX	Transmit
4	RX	Receive
5	TX	Transmit
6	RX	Receive
7	VCC	Power supply
8	GND	Ground
9	TX	Transmit
10	RX	Receive
11	VCC	Power supply
12	GND	Ground
13	TX	Transmit
14	RX	Receive
15	VCC	Power supply
16	GND	Ground



#### Procedure

1. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins.
2. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
3. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
4. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
5. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
6. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
7. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.
8. Connect the microcontroller pins TX+, TX-, RX+, and RX- to the transceiver pins TX+, TX-, RX+, and RX-.

